



The Porsche 914/1974





The Porsche 914. Technical data. 1974

		914	914-2.0
Engine	Number of cylinders	4	4
	Bore/stroke	93/66 mm (3.66/2.60 in.)	94/71 mm (3.70/2.79 in.)
	Displacement	1795 ccm. (109.5 cu. in.)	1971 ccm. (120.3 cu. in.)
	Compression ratio	7.3:1	7.6:1
	Maximum torque	13.0 mkg (94.0 ft. lbs.) at 3400 rpm	15.0 mkg (105.0 ft. lbs.) at 3500 rpm
Chassis and suspension	Front suspension	wishbones and shock absorber struts	wishbones and shock absorber struts
	Rear suspension	semi-trailing arms	semi-trailing arms
	Foot brakes	4-wheel disc brakes	4-wheel disc brakes
Electrical equipment	Alternator	700 watt/12 volt - 45 amp/hour	700 watt/12 volt - 45 amp/hour
	Battery	battery and coil	battery and coil
Wheels		5 1/2 J x 15 steel	5 1/2 J x 15 steel
Tires		165 SR 15 tubeless	165 HR 15 tubeless
Dimensions	Length/width/height (unladen)	4095/1650/1230 mm (161.2/65/48.4 in.)	4095/1650/1230 mm (161.2/65/48.4 in.)
Weights	Unladen weight (DIN standard)	970 kg (2139 pounds)	970 kg (2139 pounds)
	Permissible gross weight	1220 kg (2690 pounds)	1220 kg (2690 pounds)
Performance	Maximum speed	173 km/h (107 mph.) approx.	185 km/h (115 mph.) approx
	Acceleration 0-100 km/h (0-62 mph.) at DIN unladen weight + 1/2 payload	14 seconds	11 seconds
	Fuel consumption (average)	approx. 12 l/100 km (19.5 US mpg.)	approx. 12 l/100 km (19.5 US mpg.)

Optional equipment for both models

Appearance group

Steering wheel with leatherette cover.
Center console with clock, oil temperature gauge and voltage meter.
Leather boot for shift lever.
Dual-tone horn.
Fog lights in bumpers.

Performance group

Pressure cast alloy wheels.
Front and rear stabilizer bars.
Front spoiler.

In some cases, the cars pictured in this catalog have been equipped with items which are optional or not available in the United States. Your local authorized Porsche Audi dealer will be glad to show you the latest list of standard equipment for this market, as well as all of the available options. Design and equipment specifications are subject to change without notice.

