


VOLVO

122S Two-door Sedan
122S Four-door Sedan
122S Station Wagon
1800S Touring coupe
544 Two-door Sports Sedan





AB VOLVO

Göteborg

Sweden

Importers:
Volvo Import, Inc.,
452 Hudson Terrace, Englewood Cliffs, New Jersey

Distributors:
Volvo Distributing, Inc.,
452 Hudson Terrace, Englewood Cliffs, New Jersey

Swedish Motor Import, Inc.,
3301 West 12th Street,
Houston 24, Texas

Volvo Western Distributing, Inc.,
12925 Riverside Drive,
Sherman Oaks, Calif.

In Canada:
Volvo (Canada) Ltd.,
Head Office: 440 Comstock Road, Scarborough (Toronto), Ont.

Branch Office: 1090 W. Georgia St., Vancouver 5, B. C.

VOLVO 122 S



Two-door Sedan (13244)
Four-door Sedan (12244)
Engine 90 b.h.p. SAE.
Four-speed, fully synchronized transmission
Disc brakes front, drum brakes rear.

Wheel base 102½"
Track 51¾"
Overall length 175"
Curb weight, two-door approx. 2360 lb.
Curb weight, four-door approx. 2400 lb.



Station Wagon (22244)
Engine 90 b.h.p. SAE.
Four-speed, fully synchronized transmission.
Drum brakes.
Cargo space
with rear seat up approx. 40 cu. ft
with rear seat down approx. 65 cu. ft

Wheel base 102½"
Track 51¾"
Overall length 176½"
Curb weight approx. 2600 lb.

VOLVO P 1800 S



Touring coupe (18344, 18345)
Engine 108 b.h.p. SAE.
Four-speed, fully synchronized transmission (18344).
Four-speed fully synchronized transmission with overdrive (18345).
Disc brakes front, drum brakes rear.

Wheel base 96½"
Track 51¾"
Overall length 173¼"
Curb weight approx. 2490 lb.

VOLVO 544



Two-door Sports Sedan (11244)
Engine 90 b.h.p. SAE.
Four-speed, fully synchronized transmission.
Drum brakes.

Wheel base 102½"
Track, front 51"
Track, rear 51¾"
Overall length 175"
Curb weight approx. 2220 lb.

90 b.h.p. SAE engine (B 18 D)
Four-cylinder, overhead valves, 5-bearing crankshaft.
Bore 3.313"
Stroke 3.15"
Displacement 109 cu.in.
Compression ratio 8.5:1
Max. output 90 b.h.p. SAE at 5000 r.p.m.
Max. torque 105 lb.ft. SAE at 3500 r.p.m.
Twin SU horizontal carburetors.
Full-flow oil filter.

108 b.h.p. SAE sports engine (B 18 B)
Same construction and dimension as the B 18 D engine.
Compression ratio 9.5:1
Max. output 108 b.h.p. SAE at 5800 r.p.m.
Max. torque 110 lb.ft. at 4000 r.p.m.
Twin SU horizontal carburetors.
Full-flow oil filter.
Oil cooler.

Cooling system
Thermostat-controlled water circulation.

Battery
Voltage 12 V

Generator
Effect max. 360 W

Starter motor
Output 1 h.p.

Clutch
Single dry disc.

Transmission
4-speed, fully synchronized.

Rear axle
Hypoid type.

Steering gear
Cam and roller type.

Front suspension
Independent. Coil springs and stabilizers.

Rear suspension
Support arms, torque rods and track bar. Coil springs.

Shock absorbers
Double-acting, hydraulic, telescopic shock absorbers front and rear.

Wheels and tires
All wheels balanced. Tubeless 6.00—15" tires.

Station Wagon: 6.40—15".
1800 S: Braced-tread sports tires 165—15".

Foot brake
122 S Sedans and Volvo 1800 S:
Disc brakes front. Drum brakes rear.

122 S Station Wagon and Volvo 544:
Duo-Servo drum brakes.

Handbrake
Operates separately on rear wheels.

Body
All-welded, integral steel body. Completely rust-protected. Closed sections oil-mist sprayed.
Undercoated wheel wells.

Gas tank
Located at rear.
Volvo 544: 10 US gallons.
Other models: 12 US gallons.

Lighting equipment
Standard sealed beam headlights. Flasher type direction indicators. Combined stop and tail lights. Internal lighting and rheostat-controlled instrument lighting.

122 S Series and Volvo 1800 S:
Back-up light.

Instrumentation
Speedometer, odometer and trip meter, fuel gauge and water temperature gauge, warning lamps for charging, oil pressure, full headlights and direction indicators. Volvo 1800 S also equipped with tachometer, strip-type temperature gauges for water and oil, pressure gauge for oil, and electric clock.

Other standard equipment
Foot dimmer switch, direction indicator lever with automatic return, heater and ventilation equipment, thermostat-controlled heater, two-speed fan, electric windshield wipers and nozzles for windshield washers, padded sun visors, dazzle-free rear view mirror, cigarette lighter, ashtrays, tool kit and jack, spare wheel, safety belts for front seats and safety belt attachments for rear seat.

The factory reserves the right to modify prices, design and equipment.